

- **Part Number:** 1910
- **Part Number Title:** Occupational Safety and Health Standards
- **Subpart:** 1910 Subpart Z
- **Subpart Title:** Toxic and Hazardous Substances
- **Standard Number:** 1910.1000 TABLE Z-3
- **Title:** TABLE Z-3 Mineral Dusts
- **GPO Source:** e-CFR

TABLE Z-3 Mineral Dusts

Substance	mppcf ^a	mg/m ³
Silica:		
Crystalline		
Quartz (Respirable) ^f	250 ^b ----- %SiO ₂ + 5	10 mg/m ^{3 e} ----- % SiO ₂ + 2
Cristobalite: Use ½ the value calculated from the count or mass formulae for quartz. ^f		
Tridymite: Use ½ the value calculated from the formulae for quartz ^f		
Amorphous, including natural diatomaceous earth	20	80 mg/m ³ ----- %SiO ₂
Silicates (less than 1% crystalline silica):		
Mica	20	
Soapstone	20	
Talc (not containing asbestos)	20 ^c	
Talc (containing asbestos) Use asbestos limit		
Tremolite, asbestiform (see 29 CFR 1910.1001)		
Portland cement	50	
Graphite (Natural)	15	
Coal Dust:		

Substance	mppcf ^a	mg/m ³
Respirable fraction less than 5% SiO ₂		2.4 mg/m ³ _e
		10 mg/m ³ _e
Respirable fraction greater than 5% SiO ₂		$\frac{\text{---}}{\% \text{SiO}_2 + 2}$
Inert or Nuisance Dust: ^d		
Respirable fraction	15	5 mg/m ³
Total dust	50	15 mg/m ³

Note-Conversion factors - mppcf × 35.3 = million particles per cubic meter = particles per c.c.

^a Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques.

^b The percentage of crystalline silica in the formula is the amount determined from airborne samples, except in those instances in which other methods have been shown to be applicable.

^c Containing less than 1% quartz; if 1% quartz or more, use quartz limit.

^d All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by this limit, which is the same as the Particulates Not Otherwise Regulated (PNOR) limit in Table Z-1.

^e Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics:

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of an AEC (now NRC) instrument. The respirable fraction of coal dust is determined with an MRE; the figure corresponding to that of 2.4 mg/m³ in the table for coal dust is 4.5 mg/m^{3K}.

^f This standard applies to any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or is otherwise not in effect.

[58 FR 35340, June 30, 1993; 58 FR 40191, July 27, 1993, as amended at 61 FR 56831, Nov. 4, 1996; 62 FR 1600, Jan. 10, 1997; 62 FR 42018, Aug. 4, 1997; 81 FR 16861, March 25, 2016; 81 FR 60272-60273, September 1, 2016]

UNITED STATES DEPARTMENT OF LABOR

Occupational Safety & Health Administration
200 Constitution Ave NW
Washington, DC 20210
800-321-6742 (OSHA)
TTY
www.OSHA.gov

FEDERAL GOVERNMENT

White House
Severe Storm and Flood Recovery
Assistance
Disaster Recovery Assistance
DisasterAssistance.gov
USA.gov
No Fear Act Data
U.S. Office of Special Counsel

OCCUPATIONAL SAFETY & HEALTH

Frequently Asked
Questions
A - Z Index
Freedom of
Information Act -
OSHA
Read The OSHA
Newsletter
Subscribe to the
OSHA Newsletter
OSHA Publications
Office of Inspector
General

ABOUT THIS SITE

Freedom of Information Act - DOL
Privacy & Security Statement
Disclaimers

[Important Web Site Notices](#)

[Plug-ins Used by DOL](#)

[Accessibility Statement](#)